Pivot

Design: Sigurd Strøm & Torstein Nilsen

Pivot tables are designed to fit the comprehensive module sofas series Pivot and Pivot C

Durability

mobelfakta.no

Norsk Møbelfakta: S1374

Demountable

grøntpunkt.no

ID: 240075

Selection

1618	**Table, cube, birch, H43,5, 65x65, HPL**	
1622	**Table, cube, birch, H43,5, 130x65, HPL**	
1626	**Table, cube, birch, H43,5, Ø68, HPL**	
1949	**Table, cube, birch, H53, 65x65, HPL**	
1951	**Table, cube, birch, H53, 130x65, HPL**	
1952	**Table, cube, birch, H53, Ø68, HPL**	
1868	**Laptop table, birch, 50x25x35, HPL**	

Options

1032	**Table leg, bolt, H43,5, straight, powder painted Ultra shine, per leg**	W: 1 cm	H: 22 cm	D: 48 cm
1959	**Table leg, bolt, H43,5, arc, powder painted Ultra shine, per leg**	W: 15 cm	H: 22 cm	D: 46 cm
3449	**Table leg, pipe, H53, powder painted black, per leg**	W: 2 cm	H: 31,5 cm	D: 5 cm
1960	**Table leg, tube, metallic powder painted, per leg (extra)**	W: 2 cm	H: 22 cm	D: 5 cm
1961	**Table leg, tube, metallic powder painted, per leg (extra)**	W: 2 cm	H: 31,5 cm	D: 5 cm

Construction

Chassis in powder coated steel.
MDF table top with HPL top.
Straight edge with ABS edge list.
Standard selection: Birch, oak, white and black.

Legs

Standard leg is bolt leg powder coated in Jotun Ultrashine.
Tube leg black powder coated (RAL 9011) and other legs available for no extra charge.
Find leg alternatives after the tables, including legs in other colors.
Hard plastic pads.

Tabletop

Other solid color surfaces can be provided on request.
For HPL in "Elegant Oak F5374" there might be color differences versus other oak.

Mounting

Legs must be mounted on table tops.

Recycling

All steel parts are recyclable. During surface treatment, degreasing with alkaline washing takes place. After separation, the oil goes for destruction. Varnishing is done electrostatically with epoxy powder that gives minimal pollution. The plastic parts used are recyclable. All padding and frames are made of foam completely without freons. Only water-based and solvent free adhesives and hot melt adhesives are used.

VAD AS

Sandvikgata 14	www.vad.no
6250 Stordal	info@vad.no
Norway	+47 975 44 020